

Table 2. Confidence intervals (95%) for the amount of moisture lost to evapotranspiration before 24 tall fescue entries from data set 12AFA1 reach 75, 50, and 25% green cover. Entries are ranked based on their ET₅₀ values.

Rank	Selection	ET ₇₅	ET ₅₀	ET ₂₅
1.	ATF1434 E+	11.47 to 12.20	14.45 to 14.97	17.16 to 18.02
2.	ATF1458 E+	10.41 to 11.44	14.03 to 14.78	17.26 to 18.52
3.	ATF1434 E-	11.13 to 11.95	13.97 to 14.55	16.53 to 17.42
4.	ATF615 E+	10.70 to 11.34	13.66 to 14.12	16.41 to 17.11
5.	ATF1375 E+	9.519 to 10.57	13.50 to 14.26	17.08 to 18.35
6.	ATF1377 E+	10.87 to 11.46	13.59 to 14.00	16.12 to 16.73
7.	ATF1458 E-	10.18 to 11.08	13.45 to 14.09	16.40 to 17.40
8.	ATF1035	10.08 to 11.08	13.36 to 14.07	16.30 to 17.40
9.	ATF1254	10.80 to 11.35	13.50 to 13.89	16.03 to 16.60
10.	ATF1258 E-	9.916 to 10.81	13.28 to 13.91	16.34 to 17.33
11.	Signia	10.17 to 11.00	13.27 to 13.86	16.10 to 16.99
12.	ATF1376 LE	10.33 to 11.03	13.26 to 13.74	15.96 to 16.68
13.	Rebel Exeda	10.57 to 11.27	13.24 to 13.73	15.69 to 16.41
14.	ATF610 E+	9.467 to 10.37	13.09 to 13.74	16.40 to 17.42
15.	ATF1377 E-	10.04 to 10.74	12.92 to 13.41	15.58 to 16.30
16.	ATF1402 E+	9.406 to 10.20	12.79 to 13.35	15.92 to 16.77
17.	Cortez II	9.419 to 10.35	12.69 to 13.35	15.66 to 16.65
18.	ATF1375 E-	8.823 to 9.872	12.62 to 13.36	16.05 to 17.22
19.	ATF1402 E-	9.529 to 10.30	12.72 to 13.26	15.65 to 16.47
20.	Rebel XLR	10.06 to 10.52	12.82 to 13.14	15.44 to 15.90
21.	ATF1492 E-	9.820 to 10.41	12.55 to 12.97	15.11 to 15.71
22.	ATF1497 E+	8.978 to 9.768	12.10 to 12.66	14.98 to 15.78
23.	ATF1497 E-	9.015 to 9.662	11.95 to 12.40	14.68 to 15.34
24.	Crackle	8.115 to 8.879	11.18 to 11.72	14.02 to 14.79

